

Speed is Power

M3 MOBILE

SL10 Series

 **GMS Certified**

Retail Targeted Product



4 Front Keys
Weight : 260g
Battery: 4,000mAh



Alpha Numeric Keys
Weight : 292g
Battery: 4,400mAh



Slim Design, Light Weight



Data-only / LTE type available



Removable Battery



Reasonable Price with Quad-Core CPU



Physical Keys available



Trigger Handle, Cradle, Arm Band and more



Arm Band



Trigger Handle



Cradle



Bluetooth™



kalipso



Specification

	SL10-N	SL10-W	SL10K-N	SL10K-W
DIMENSION (W x H x D)	156 x 74 x 17mm		155.8 x 72 x 25 mm	
WEIGHT	260 g		292 g	
DISPLAY	5.0 in. HD		4 in. WVGA	
TOUCH	Capacitive touch		Capacitive touch	
BATTERY	Li-ion 3.8 V 4,000 mA		Li-ion 3.8 V 4,400 mA	
SIM / SAM	1 SIM		1 SIM	
PHYSICAL KEYS	4 physical keys + 2 side scan + volume		17 physical keys + 2 side scan + volume	
PROCESSOR	1.44 GHz Quad-core processor		1.44 GHz Quad-core processor	
OS	Android 8.1 (GMS only SL10-N)		Android 8.1	
MEMORY	RAM 2G / ROM 16G		RAM 2G / ROM 16G	
INTERFACE	Micro USB		Micro USB	
WWAN	CMCC 5M : LTE 1 / 2 / 3 / 4 / 7 / 17 / 20 / 38 / 39 / 40 / 41 WCDMA 1 / 2 / 5 / 8 TD-SCDMA 34 / 39 GSM 2 / 3 / 5 / 8	Not Applicable	CMCC 5M : LTE 1 / 2 / 3 / 4 / 7 / 17 / 20 / 38 / 39 / 40 / 41 WCDMA 1 / 2 / 5 / 8 TD-SCDMA 34 / 39 GSM 2 / 3 / 5 / 8	Not Applicable
WLAN	IEEE 802.11 a/b/g/n, Frequency 2.4G+5.8G dual band WIFI		IEEE 802.11 a/b/g/n, Frequency 2.4G+5.8G dual band WIFI	
BLUETOOTH	Bluetooth Class I 4.0 LE		Bluetooth Class I 4.0 LE	
GPS	GPS with A-GPS (Glonass, BeiDou)	Not Applicable	GPS with A-GPS (Glonass, BeiDou)	Not Applicable
SCANNER	1D Laser, 2D Imager (SE4710)		1D Laser, 2D Imager (SE4710)	
CAMERA	8.0 M(Rear), 2.0 m(Front), LED Flash		8.0 M(Rear), 2.0 m(Front), LED Flash	
RFID	NFC (13.56MHz) Peer-to-peer, card reader, card emulation ISO 14443 A / B, ISO 15693		NFC (13.56MHz) Peer-to-peer, card reader, card emulation ISO 14443 A / B, ISO 15693	
TEMPERATURE	Operating -10°C to 50°C Storage -30°C to 70°C		Operating -10°C to 50°C Storage -30°C to 70°C	
HUMIDITY	0% to 95% non-condensing		0% to 95% non-condensing	
DROP TEST	1.2 m / 1.5m (with Boots)		1.2 m / 1.5m (with Boots)	
IP RATING	IP65		IP65	